

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

LUSSO

TECHNICAL CHARACTERISTICS

Available Formats:	12X48		
Style Description:	Wood	Glaze Application Method:	Inkjet
Thickness in mm:	7 mm	Number of Faces/Screens:	8
Modular Suitability:	No	Number of Punches/Molds:	1
Application:	Residential	Body Type:	Porcelain
Rectified or Pressed:	Pressed	Color Body:	
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Flat Matte
		Recommended Grout Joint:	3 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	Paloma: 0.09 Betulla: 0.10 Ivory: 0.13 Miele: 0.11	Chemical Resistance:	HA-A-LA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	0.68
Scratch Hardness (MOHS)	8	Breaking Strength:	1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	150°C (+)
PEI/Abrasion Resistance:	III	Deep Abrasion Test <175mm ² :	No

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.