

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

ALBERO

TECHNICAL CHARACTERISTICS

Available Formats:	8x24		
Style Description:	Wood	Glaze Application Method:	Standard Screen
Thickness in mm:	8.5 mm	Number of Faces/Screens:	8
Modular Suitability:	No	Number of Punches/Molds:	
Application:	Residential, Commercial	Body Type:	Ceramic
Rectified or Pressed:	Pressed	Color Body:	Glazed
Recycled Content: Post or Pre Customer	No	Surface Type:	Satin
		Recommended Grout Joint:	3 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	Between 6% and 10%	Chemical Resistance:	≥ class GB
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	≥ 0.4
Scratch Hardness (MOHS)	Resistant	Breaking Strength:	≥ 500N
Frost Resistant:	No	Thermal Shock Resistance:	No
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm ² :	No

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.