

# NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

**Chelsea**

## TECHNICAL CHARACTERISTICS

|                                           |                                                                                         |                           |                                                                                           |
|-------------------------------------------|-----------------------------------------------------------------------------------------|---------------------------|-------------------------------------------------------------------------------------------|
| Available Formats:                        | 2.5x10                                                                                  |                           |                                                                                           |
| Style Description:                        | Brick                                                                                   | Glaze Application Method: | Inkjet                                                                                    |
| Thickness in mm:                          | 9mm                                                                                     | Number of Faces/Screens:  | Mainstreet- 119<br>Highline- 61<br>Coffee House- 122<br>Whitehall- 106<br>Kings Road- 106 |
| Application:                              | Wall interior/exterior<br>Floor Interior/exterior<br>Pool waterline<br>Fireplace hearth | Number of Punches/Molds:  | 6                                                                                         |
| Rectified or Pressed:                     | Pressed                                                                                 | Body Type:                | Porcelain                                                                                 |
| Recycled Content:<br>Post or Pre Customer | 38.5%                                                                                   | Surface Type:             | Undulated                                                                                 |
|                                           |                                                                                         | Recommended Grout Joint:  | 3mm                                                                                       |

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

|                              |      |                           |            |
|------------------------------|------|---------------------------|------------|
| Water Absorption:            | <.5% | Chemical Resistance:      | GLA/GHA/GA |
| Shade Variation (1, 2, 3, 4) | 4    | Dynamic COF:              | .68        |
| Frost Resistant:             | Yes  | Breaking Strength:        | 35N/mm2    |
| PEI/Abrasion Resistance:     | 4    | Thermal Shock Resistance: | Yes        |

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.*