

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Dolomina

TECHNICAL CHARACTERISTICS

Available Formats:	Polished and Matte 12x24, 24x48, 3" hex mosaic (matte only)		
Style Description:	Dolomite marble	Glaze Application Method:	Inkjet
Thickness in mm:	8.3mm	Number of Faces/Screens:	12x24- 42 24x48- 16
Modular Suitability:	No	Number of Punches/Molds:	1
Application:	Residential • Wall wet/dry • Floor wet/dry • Hearth • Exterior wall • Exterior floor (matte) Light Commercial • Wall wet/dry • Hearth • Floor dry (matte) • Exterior wall	Body Type:	Porcelain
Rectified or Pressed:	Rectified	Color Body:	No
Recycled Content: Post or Pre Customer	0%	Surface Type:	Flat matte/polished
		Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Chemical Resistance:	EN ISO 10545-14 Class 3
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	>0.7
Scratch Hardness (MOHS)	5	Breaking Strength:	2023N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	3 Polished 4 Matte	Deep Abrasion Test <175mm ² :	EN ISO 10545-7 class 4 Pass

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.