

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Kentia

TECHNICAL CHARACTERISTICS

Available Formats:	12x36		
Style Description:	Floral	Glaze Application Method:	Inkjet
Thickness in mm:	9.2mm-9.4mm	Number of Faces/Screens:	1
Application:	Residential <ul style="list-style-type: none">Interior wall wet/dry Commercial <ul style="list-style-type: none">Interior wall wet/dry	Number of Punches/Molds:	1
Rectified or Pressed:	Rectified	Body Type:	White body Ceramic
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Flat and Relief
		Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	>10%	Chemical Resistance:	EN ISO 10545-13 <ul style="list-style-type: none">Acid- GLABase-GLBUA EN-ISO 10545-14 <ul style="list-style-type: none">5 stain resistance
Shade Variation (1, 2, 3, 4)	1	Dynamic COF:	N/A
Frost Resistant:	No	Breaking Strength:	>20N/mm ²
PEI/Abrasion Resistance:	N/A	Thermal Shock Resistance:	Resistant

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.