

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Sol

TECHNICAL CHARACTERISTICS

Available Formats:	6'x6'		
Style Description:	Glossy solid color & deco	Glaze Application Method:	Spray
Thickness in mm:	10mm	Number of Faces/Screens:	1
Application:	Vertical wall, Submerged vertical applications	Number of Punches/Molds:	1
Rectified or Pressed:	Pressed	Body Type:	Porcelain
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Glossy
		Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5	Chemical Resistance:	Yes
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Frost Resistant:	Yes	Breaking Strength:	1300 N
PEI/Abrasion Resistance:	3	Thermal Shock Resistance:	Yes

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.