

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Ethereal

TECHNICAL CHARACTERISTICS

Available Formats:	12x36"		
Style Description:	Cross cut travertine Troweled 3 rd fire	Glaze Application Method:	Inkjet
Thickness in mm:	10-11mm	Number of Faces/Screens:	2
Application:	Residential <ul style="list-style-type: none">Interior Wall Dry/Wet Commercial <ul style="list-style-type: none">Interior wall Dry/Wet	Number of Punches/Molds:	1
Rectified or Pressed:	Rectified	Body Type:	White body Ceramic
Recycled Content: Post or Pre Customer	35%	Surface Type:	Deco- High relief Field- matte flat
		Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	12%<E<18%	Chemical Resistance:	EN-ISO10545-13 <ul style="list-style-type: none">GLA, GHA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	N/A
Frost Resistant:	No	Breaking Strength:	600N
PEI/Abrasion Resistance:	N/A	Thermal Shock Resistance:	Resists

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.