

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Reliefs

TECHNICAL CHARACTERISTICS

Available Formats:	24x48		
Style Description:	Field Relief	Glaze Application Method:	Unglazed
Thickness in mm:	9mm	Number of Faces/Screens:	1
Application:	Residential • Interior Wall Dry/Wet • Exterior Wall • Interior floor (Field only) Commercial • Interior wall dry/wet • Exterior wall • Interior floor (field only)	Number of Punches/Molds:	1
Rectified or Pressed:	Rectified	Body Type:	Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Flat field Relief decos
		Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.2%	Chemical Resistance:	EN ISO 10545-13 • GA/LA/HA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	>.5 field N/A relief
Frost Resistant:	Yes	Breaking Strength:	>35N/mm2
PEI/Abrasion Resistance:	N/A	Thermal Shock Resistance:	Resists

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.

3500 SW 42nd Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)
info@iwttesoro.com | www.iwttesoro.com

