

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Native Wood

TECHNICAL CHARACTERISTICS

Available Formats:	8x48		
Style Description:	Wood Look	Glaze Application Method:	Inkjet
Thickness in mm:	8mm	Number of Faces/Screens:	30
Modular Suitability:	No	Number of Punches/Molds:	N/A
Application:	Residential - Interior wall wet/dry - Exterior wall wet/dry - Interior Floor Commercial - Interior wall wet/dry - Exterior wall wet/dry - Interior Floor	Body Type:	Porcelain
Rectified or Pressed:	Pressed	Color Body:	No
Recycled Content: Post or Pre Customer	Pre customer >64%	Surface Type:	Matte
		Recommended Grout Joint:	3/16 th inch

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.1%	Chemical Resistance:	Not affected
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>.42
Scratch Hardness (MOHS)	7	Breaking Strength:	Complies
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.

3500 SW 42nd Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)
info@iwttesoro.com | www.iwttesoro.com