

# NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

**Dama**

## TECHNICAL CHARACTERISTICS

Available Formats:	10x10, 2.5x10		
Style Description:	Marble, checkerboard	Glaze Application Method:	Inkjet
Thickness in mm:	8mm	Number of Faces/Screens:	2.5x10- 90 10x10- 16
Modular Suitability:	No	Number of Punches/Molds:	2
Application:	Residential <ul style="list-style-type: none"> <li>• Interior Floor</li> <li>• Interior wall wet/dry</li> <li>• Exterior wall</li> <li>• Exterior floor</li> <li>• Pool waterline</li> <li>• Firelace hearth</li> </ul> Commercial <ul style="list-style-type: none"> <li>• Interior Floor</li> <li>• Interior wall wet/dry</li> <li>• Exterior wall</li> </ul>	Body Type:	Porcelain
Rectified or Pressed:	Pressed	Color Body:	No
Recycled Content: Post or Pre Customer	20%	Surface Type:	Undulated
Country of Origin	Italy	Recommended Grout Joint:	3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<.5%	Chemical Resistance:	GLA, GHA, GA
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	.68 R10
Scratch Hardness (MOHS)	7	Breaking Strength:	48 N/mm <sup>2</sup>
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	PEI 3- Nero, Pulpis PEI 4- All other colors	Deep Abrasion Test <175mm <sup>2</sup> :	N/A

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.

3500 SW 42<sup>nd</sup> Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)  
info@iwttesororo.com | www.iwttesororo.com