

# NEW PRODUCT SERIES

## Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

**Groves**

### TECHNICAL CHARACTERISTICS

|                                           |                                                                                                                                                                                                                                                                                                   |                           |                      |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|----------------------|
| Available Formats:                        | 10x63, 36x36                                                                                                                                                                                                                                                                                      |                           |                      |
| Style Description:                        | Wood look                                                                                                                                                                                                                                                                                         | Glaze Application Method: | Inkjet               |
| Thickness in mm:                          | 9mm                                                                                                                                                                                                                                                                                               | Number of Faces/Screens:  | 10x63- 9<br>36x36- 4 |
| Modular Suitability:                      | No                                                                                                                                                                                                                                                                                                | Number of Punches/Molds:  | 2                    |
| Application:                              | Residential <ul style="list-style-type: none"><li>• Interior floor</li><li>• Interior wall wet/dry</li><li>• Exterior wall</li><li>• Exterior floor</li></ul> Commercial <ul style="list-style-type: none"><li>• Interior floor</li><li>• Interior wall wet/dry</li><li>• Exterior wall</li></ul> | Body Type:                | Porcelain            |
| Rectified or Pressed:                     | Rectified                                                                                                                                                                                                                                                                                         | Color Body:               | No                   |
| Recycled Content:<br>Post or Pre Customer | N/A                                                                                                                                                                                                                                                                                               | Surface Type:             | Slight undulation    |
| Country of Origin                         | Italy                                                                                                                                                                                                                                                                                             | Recommended Grout Joint:  | 2mm                  |

### PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

|                              |      |                                             |                       |
|------------------------------|------|---------------------------------------------|-----------------------|
| Water Absorption:            | <.5% | Chemical Resistance:                        | GLA, GHA, GA          |
| Shade Variation (1, 2, 3, 4) | 2    | Dynamic COF:                                | >.42                  |
| Scratch Hardness (MOHS)      | 6    | Breaking Strength:                          | R>40N/mm <sup>2</sup> |
| Frost Resistant:             | Yes  | Thermal Shock Resistance:                   | <7MK(-1)              |
| PEI/Abrasion Resistance:     | 4    | Deep Abrasion Test<br><175mm <sup>2</sup> : | Yes                   |

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.

3500 SW 42<sup>nd</sup> Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)  
info@iwttesoro.com | www.iwttesoro.com

