

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

BALI

TECHNICAL CHARACTERISTICS

Available Formats:	6x6 / 6x24		
Style Description:	Highly glossy reflective surface finish	Glaze Application Method:	Inkjet
Thickness in mm:	9 mm	Number of Faces/Screens:	12
Application:	Residential Wall/Exterior Wall/Shower Wall/Pool/Fireplace	Number of Punches/Molds:	2
Rectified or Pressed:		Body Type:	
Recycled Content: Post or Pre Customer	10%	Surface Type:	Glossy
		Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≤ 0.5%	Chemical Resistance:	Yes
Shade Variation (1, 2, 3, 4)	4	Dynamic COF:	
Frost Resistant:	Yes	Breaking Strength:	Passed
PEI/Abrasion Resistance:		Thermal Shock Resistance:	Passed

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.