

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Zafira II

TECHNICAL CHARACTERISTICS

Available Formats:	18x18		
Style Description:	Cross cut/Cement	Glaze Application Method:	Inkjet, Rotocolor
Thickness in mm:	8mm	Number of Faces/Screens:	6 faces
Modular Suitability:	No	Number of Punches/Molds:	2
Application:	Residential <ul style="list-style-type: none"> • Wall wet/Dry • Floor Interior Dry Commercial <ul style="list-style-type: none"> • Wall Wet/Dry 	Body Type:	Red Body Ceramic
Rectified or Pressed:	Pressed	Color Body:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Country of Origin	Ecuador	Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	6% \leq x \leq 10%	Chemical Resistance:	HA
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	x \geq .42
Scratch Hardness (MOHS)	6	Breaking Strength:	\geq 800N
Frost Resistant:	No	Thermal Shock Resistance:	No
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.