

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**Cross**

## TECHNICAL CHARACTERISTICS

|                                           |                        |                           |                 |
|-------------------------------------------|------------------------|---------------------------|-----------------|
| Available Formats:                        | 6x6 Field Tile         |                           |                 |
| Style Description:                        | Decorative             | Glaze Application Method: | Inkjet          |
| Visual Characteristics:                   | Glossy                 | Number of Faces/Screens:  | 24              |
| Thickness in mm:                          | 8.5                    | Number of Punches/Molds:  | 1               |
| Modular Suitability:                      | N/A                    | Body Type:                | Porcelain       |
| Application:                              | Residential/Commercial | Color Body Unglazed:      | No              |
| Recycled Content:<br>Post or Pre Customer | N/A                    | Surface Type:             | Smooth / Glossy |
| Rectified or Pressed                      | Pressed                | Recommended Grout Joint:  | 3/16"           |

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

|                              |       |                                             |           |
|------------------------------|-------|---------------------------------------------|-----------|
| Water Absorption:            | <0.5% | Static COF:                                 |           |
| Shade Variation (1, 2, 3, 4) | V3    | Dynamic COF:                                | ≥0.40     |
| Scratch Hardness (MOHS)      | 5     | Breaking Strength:                          | Complies  |
| Frost Resistant:             | Yes   | Thermal Shock Resistance:                   | Resistant |
| PEI/Abrasion Resistance:     | 2     | Deep Abrasion Test<br><175mm <sup>2</sup> : | N/A       |
| Chemical Resistance:         | A     |                                             |           |

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*