

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Trapezoid Pool Mosaics

TECHNICAL CHARACTERISTICS

Available Formats:	1"x1" / 1.5"x1.5" Mosaic on 12x12 mesh		
Style Description:	Pool Tile	Glaze Application Method:	Hot Fired Backside w/ Mask
Visual Characteristics:	Mosaic	Number of Faces/Screens:	4
Thickness in mm:	6.0 mm	Number of Punches/Molds:	2
Modular Suitability:	No	Body Type:	Crystal Glass on Mesh
Application:	Pool / Wall	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Glossy
Rectified:	No	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	3	Breaking Strength:	UNE-EN-ISO 10545-4 - Pass
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	N/A	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	Resistant	Frostproof	Yes

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	10.56	Pieces per Carton:	15
SqFt per Pallet:	1,045.44	Pounds per Carton:	36.75
Boxes per Pallet:	99	SqFt per Container:	20,908.8
Pallets per Container:	20		

Note: DIRECTIONAL CUT MATERIAL

Approved for Submerged applications / Certified Frost Proof