

Product Information Sheet

Series: Palladium Grey



Product Characteristics

Country of Origin	China
Body Type	Natural Marble
Thickness	10mm
Finishes	Polished
Edge Finish	Straight Cut
Recommended Grout Joint	≥2mm

Test Data

Water absorption	ASTM C503	0.22%
Compressive Strength	ASTM C503	152 Mpa
Flexural Strength	ASTM C503	14.8 Mpa
Apparent Density	ASTM C503	175.40 lb/ft ³
Frost Resistance	EN12371:2010	Resistant
Abrasion Resistance	EN 14157 Method A	Pass:15mm groove
Shade Variation	V1-5	V3

Usage Recommendations

Application		Wall	Floor
Interior	Residential	Yes	Yes
	Commercial	Yes	Yes
Exterior	Residential	Yes	No
	Commercial	Yes	No
Product is also suitable for Hearth Surround, Fireplace, Shower Walls & Floors, & Backsplashes.			

Installation Recommendations

- All installations, including recommendations for grout, thinset, tools, etc should refer to the most current TCNA manual. Tile Council of North America- **tcnatile.com**.
- All Tesoro Installation recommendations are suggestions. Specific Install questions should be directed to your installation professional.
- Confirm the layout and grout joint thickness with a dry lay and mix product from different boxes to ensure the desired look meets expectations.
- Always Preseal natural stone products before grouting and is recommended to seal again after grouting.
- Inspect all material prior to installation for defects and customer satisfaction. Installation constitutes acceptance.
- Stone is a natural product. Variations in color, tone, shading, veining, and characteristics are inherent to this material and can vary from different lots. This must be considered before use.